

OBEXION UD SR3 SECURITY SHUTTER

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 7: SR3
- Secured by Design Police Preferred Specifications



CERTIFIED PROTECTION AGAINST:



Forced Entry:
Bodily Force

Mitigation of opportunist intruder attempts using manual or bodily force including tools.



Forced Entry:
Power Tools

Protecting against deliberate forced entry of premises using mechanically-enhanced power tools.

Designed to resist attacks from a deliberate forced entry using bodily force and a wide selection of attack options, the Obexion SR3 Shutter caters for and is generally used in commercial areas with a high risk.

Other SR3 shutters require additional auxiliary locking that is manually engaged after the shutter has been lowered. This additional action means that the shutter can only be operated internally. The unique LockDown technology, included in every Obexion shutter, means that the Obexion SR3 shutter can be operated externally. This allows the shutter to be used on first points of entry and ensures the shutter is never left in an insecure position through an incomplete locking procedure.

LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

OBEXION UD SR3 SECURITY SHUTTER

SUITABLE APPLICATIONS INCLUDE:

- High value commercial
- Banks and Financial Institutions
- Utilities facilities

APPROVED DIMENSIONS

Minimum certified height: 2.0m Minimum certified width: 1.0m

Maximum certified height: 10.0m Maximum certified width: 8.0m

SHUTTER CURTAIN

Perforated curtain profile for vision and ventilation.
Extruded aluminium LockDown profiles.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.
Safety on close as assessment directs.

OPTIONS

Perforated curtain profile for vision and ventilation.
Anti-cut core for protection against Bespoke risks including grinder attack.

PRODUCT REFERENCE

Obexion UD SR3 Security Shutter

PERFORMANCE

Certified to LPS 1175 Issue 7 SR3

SUITABLE SUBSTRATES:

Internal and External installations complete with sub assembly steel frames as required

Certified installation onto:

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork

FRAMES/GUIDES

Heavy duty guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

OPERATION

Motorised to allow controlled ascent and descent.
240v - Low duty cycle or where limited to single phase supply.
415v - High duty cycle or for larger apertures.

