

## INTEGR8 NON STRUCTURAL SR3 SECURITY SHUTTER



### CERTIFIED PROTECTION AGAINST:



**Forced Entry: Bodily Force** Mitigation of opportunist intruder attempts using manual or bodily force including tools.



**Forced Entry: Power Tools** Protecting against deliberate forced entry of premises using mechanically-enhanced power tools.

### PRODUCT REFERENCE

Integr8 Non Structural SR3 Security Shutter

### PERFORMANCE

High strength extruded aluminium to ensure glazing and building protection

### CONCEALED SHUTTER

Specified to guard against an opportunist attack using bodily physical force and a selection of attack tools that increase mechanical advantage.

Installed in line with police approved standards. Compliant with new building guidelines.

The Integr8 Non Structural SR3 Shutter is a high performance, certified solution for properties requiring an integrated security shutter – without the requirement for a structural lintel.

Independently tested and certified product to LPCB 1175, Issue 7 by the LPCB to LPS security rating 3, this shutter system is also recognised by Secured by Design as a police preferred specification. Full customisable, the Integr8 Structural SR3 shutter is available with a wide range of finishes and colours to RAL/BS.v

### LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

## INTEGR8 NON STRUCTURAL SR3 SECURITY SHUTTER

Manufactured from extruded aluminium, the Integr8 Non Structural SR3 Shutter is reinforced by an bottom rail that contains a strengthened core. Without the structural lintel requirement, the shutter recessed into the cavity of the external wall complete with closer.

### SHUTTER CURTAIN

UltraDUO high security Grade 6063 T6  
Finish as delivered: polyester powder coated in standard RAL/BS code.  
Marine Grade PPC or anodising options including wood grain effect available.  
Perforated laths available up to 13%.

### HOOD BOX

Two part roll folded aluminium hood box with detachable front cover for maintenance.

### BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.

### FRAMES/GUIDES

Slimline guide profiles fixed direct to the structure.  
Finish as delivered: polyester powder coated in standard RAL/BS colour.

### SUITABLE SUBSTRATES:

Suitable for installation onto:

- Brickwork
- Blockwork
- Timber frame
- Structural Steel framing

### SPECIFICATION

Specified to guard against deliberate forced entry of well-protected premises using bodily physical force and a wide selection of attack tool options.

### SUITABLE APPLICATIONS:

- Commercial
- Community
- Education
- Healthcare

### ARRANGEMENT

Horizontal shutters, with roller shutter boxes concealed behind external brick leaf.

### CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.

Safety on close as assessment directs.

### OPERATION

Motorised to allow controlled ascent and descent.  
240v - Low duty cycle or where limited to single phase supply.

Manual override option for power failure.



Assessed to ISO 9001  
Cert/LPCB ref.1075



LPS 1175: Issue 7  
Cert No. 1075a



v01\_11-24