LPCB®

www.redbooklive.com

Certificate of Product Approval

Certificate Number: 1075j

lssue: 01

PRE

Charter Global Limited

1 Darwin Close Reading Berkshire RG2 0TB

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

Product

Obexion MDD security shutters

Standard

LPS 1175: Issue 8

Requirements and testing procedures for the LPCB certification and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities

ce that	Chris Hunt	11 November 2024	11 Noven	nber 2024	
Signed for BRE Global Ltd.	Verifier	Date of Issue	Date of First Issue		
TON CERTIFIC	This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).				
	To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.				
	BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com			hre	
	LPCB is a Registered Trademark	of the Building Research Establishment Ltd.			
BF1281A Rev.1.1	P	age 1 of 2	© BRE	Global Ltd, 2024	

LPCB®

Appendix to Certificate No: 1075j Charter Global Limited

Issue: 01

Security Shutters

Product Name	Model	Туре	Minimum Structural Opening Height (m)	Maximum Structural Opening Height (m)	Minimum Structural Opening Width (m)	Maximum Structural Opening Width (m)	Security Rating	LPCB Ref No.
Obexion MDD	MDD-05	Internally face fitted roller shutter incorporating solid laths	1.0	10.0	1.0	6.0	D5	1075j/01
		Externally face fitted roller shutter incorporating solid laths	1.3	10.0	1.0	6.0		
	MDD-10	Internally face fitted roller shutter incorporating solid laths	1.0	10.0	1.0	6.0	D10 (SR4)	1075j/02
		Externally face fitted roller shutter incorporating solid laths	1.3	10.0	1.0	6.0		
	MDD-15	Internally face fitted roller shutter incorporating solid laths	1.0	10.0	1.0	6.0	D15	1075j/03
		Externally face fitted roller shutter incorporating solid laths	1.3	10.0	1.0	6.0		
	MDD-20	Internally face fitted roller shutter incorporating solid laths	1.0	10.0	1.0	6.0	D20	1075j/04
		Externally face fitted roller shutter incorporating solid laths	1.3	10.0	1.0	6.0		

Approved Installation Configurations

Product Name	Configuration	Substrate				
		Reinforced brickwork/ blockwork	Reinforced concrete	Structural steelwork		
Obexion MDD	Internally or externally face fitted roller shutter	\checkmark	\checkmark	\checkmark		

Notes:

1. The installation shall be direct to the substrate and not via intermediate substrates, such as plasterboard.

2. The approval only applies to the shutters when installed strictly in accordance with the instructions and using the fixings provided with the product.

This certificate and appendix is maintained and held in force through regular surveillance activities

