CHARTER GLOBAL
PROTECTING PEOPLE | SECURING PROPERTY

INTEGR8 NON-STRUCTURAL SR3 SECURITY SHUTTER



PRODUCT REFERENCE

Integr8 Non-Structural SR3 Security Shutter

PERFORMANCE

High-strength extruded aluminium to ensure glazing and building protection

CERTIFIED PROTECTION AGAINST:

Forced Entry: **Bodily Force**

Mitigation of opportunist intruder attempts using manual or bodily force including tools.

Forced Entry: **Power Tools**

Protecting against deliberate forced entry of premises using mechanically -enhanced power tools.

CONCEALED SHUTTER

- Specified to guard against an opportunist attack using bodily physical force and a selection of attack tools that increase mechanical advantage
- Installed in-line with police approved standards
- Compliant with new building guidelines

The Integr8 Non-Structural SR3 shutter is a high-performance, certified solution for properties requiring an integrated security shutter - without the requirement for a structural lintel.

This products is independently tested and certified to LPS 1175, Issue 7 by the LPCB to SR3. It is also recognised by Secured by Design as a Police Preferred Specification.

The Integr8 Structural SR3 shutter is available with a wide range of finishes and colours to RAL/BS.

LOCKDOWN TECHNOLOGY

- No auxiliary locking required - manual or electronic
- Unique profiles lock the shutter in any stop position - fully closed or otherwise
- Allows external first point-of-entry through the shutter

CHARTER GLOBAL

INTEGR8 NON-STRUCTURAL SR3 SECURITY SHUTTER

Manufactured from extruded aluminium, the Integr8 Non-Structural SR3 security shutter has a reinforced bottom rail containing a strengthened core. Without the structural aspect of the lintel requirement, the shutter is recessed into the cavity of the external wall, complete with closer.

SPECIFICATION DESCRIPTION

- Specified to guard against deliberate forced entry of well-protected premises using bodily physical force and a wide selection of attack tool options

SUITABLE APPLICATIONS INCLUDE:

- Commercial
- Community
- Education
- Healthcare

SUITABLE SUBSTRATES

Suitable for installation onto:

- Brickwork
- Blockwork
- Timber frame
- Structural steel framing

SHUTTER CURTAIN

- UltraDUO high-security Grade 6063 T6
- Finish as delivered: Polyester powder-coated in standard RAL/BS colours available
- Marine Grade PPC or anodising options including wood grain effect available
- Perforated laths available giving up to 13% open area

APPROVED DIMENSIONS

Min certified height: **1.0m**	Min certified width: **0.6m**
Max certified height: **10.0m**	Max certified width: **8.0m**

BOTTOM RAIL

- Reinforced extruded aluminium section with strengthened core

FRAMES/GUIDES

- Slimline guide profiles fixed direct to the structure
- Finish as delivered: Polyester powder-coated in standard RAL/BS colours available

HOOD BOX

- Two part, roll-folded aluminium hood box with detachable front cover for maintenance

CONTROLS

Full range of compatible controls including:

- Push button switch
- Key switch
- Radio control
- Integration into existing building management systems and third party alarm
- Safety on close as assessment directs

OPERATION

- Motorised to allow controlled ascent and descent
- 240v - low duty cycle or where limited to single phase supply
- Manual override option for power failure

Assessed to ISO 9001
Cert/LPCB ref: 1075

LPS 1175: Issue 8
Cert No. 1075a

Secured by Design
Official Police Security Initiative

1 Darwin Close, Reading RG2 0TB United Kingdom
+44 (0)845 050 8705 enquiries@charter-global.com **www.charter-global.com**