CHARTER GLOBAL
PROTECTING PEOPLE | SECURING PROPERTY

OBEXION DATA SHEET

OBEXION UDC-05 SECURITY SHUTTER



PRODUCT REFERENCE

Obexion UDC-05 (SR3) Security Shutter

PERFORMANCE

Certified to LPS 1175 Issue 8 C5 (SR3)

CERTIFIED PROTECTION AGAINST:

Forced Entry: Bodily Force

Mitigation of opportunist intruder attempts using manual or bodily force including tools.

Forced Entry: Power Tools

Protecting against deliberate forced entry of premises using mechanically -enhanced power tools.

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8 C5 (SR3)
- Secured by Design Police Preferred Specification

Designed to resist attacks from a deliberate forced entry using bodily force and a wide selection of attack options, the Obexion UDC-05 shutter caters for and is generally used in commercial areas with a high risk.

LOCKDOWN TECHNOLOGY

- No auxiliary locking required - manual or electronic
- Unique profiles lock the shutter in any stop position - fully closed or otherwise
- Allows external first point-of-entry through the shutter

CHARTER GLOBAL

OBEXION UDC-05 SECURITY SHUTTER

SPECIFICATION DESCRIPTION

Horizontal security shutter to protect against deliberate forced entry of well-protected premises using bodily physical force and a wide selection of attack tools.

SUITABLE APPLICATIONS INCLUDE:

- High-value commercial
- Banks and financial instituations
- Utilities facilities

SUITABLE SUBSTRATES

- Internal and external installations complete with sub-assembly steel frames as required

Certified installation onto:

- Brickwork
- Blockwork
- Concrete
- Structural steelwork

SHUTTER CURTAIN

- Twin-wall extruded aluminium profile with Lockdown feature
- Finish as delivered: Polyester powder-coated in standard RAL/BS colours available

OPTIONS

- Perforated curtain profile for vision and ventilation
- Anti-cut core for protection against bespoke risks including grinder attack

APPROVED DIMENSIONS

Min certified height: **1.0m**	Min certified width: **0.6m**
Max certified height: **10.0m**	Max certified width: **8.0m**

BOTTOM RAIL

- Reinforced extruded aluminium section with strengthened core
- Finish as delivered: Polyester powder-coated in standard RAL/BS colours available

FRAMES/GUIDES

- Heavy-duty guide profiles anchored direct to the structure
- Finish as delivered: Polyester powder-coated in standard RAL/BS colours available

CONTROLS

Full range of compatible controls including:

- Push button switch
- Key switch
- Radio control
- Integration into existing building management systems and third party alarm
- Safety on close as assessment directs

OPERATION

- Motorised to allow controlled ascent and descent
- 240v - low duty cycle or where limited to single phase supply
- 415v - high duty cycle or for larger apertures

Assessed to ISO 9001
Cert/LPCB ref: 1075

LPS 1175: Issue 8
Cert No. 1075p

Secured by Design
Official Police Security Initiative

1 Darwin Close, Reading RG2 0TB United Kingdom
+44 (0)845 050 8705 enquiries@charter-global.com **www.charter-global.com**